

SAFETY DATA SHEET



SECTION 1: IDENTIFICATION

COMPANY NAME: AMERICAN INDUSTRIES, INC. **PRODUCT NAME:** 2001
ADDRESS LINE 1: 4300 Kahn Drive, Box 1405 **PRODUCT CODE:** 2211
ADDRESS LINE 2: Lumberton, NC 28359-1405 USA **PRODUCT USE:** Epoxy Putty
TELEPHONE NUMBERS: 800-753-5153 (or) 910-738-7224 **SDS FILE ID:** 2211.10
EMERGENCY PHONE: CHEMTREC 1-800-424-9300 **SDS DATE:** 2026-01-07
REPLACES VERSION DATED: 2022-04-11 and all prior versions

SECTION 2: HAZARDS IDENTIFICATION

OSHA/HCS status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture: SKIN CORROSION/IRRITATION - Category 2
EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
CARCINOGENICITY – Category 1A
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) – Category 3
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 28.2% (oral), 72.7% (dermal), 86.9% (inhalation)

GHS label elements:

Hazard pictograms:



Signal word: Danger

Hazard statements: Causes irritation. May cause serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause cancer.

Precautionary statements:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid breathing dust. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental Label elements Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Emits toxic fumes when heated.

Hazards not otherwise classified: None Known

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture: Mixture

Ingredient name	% by weight	CAS number
Talc, not containing asbestiform fibers	30 – 60	14807-96-6
glass, oxide, chemicals	10 – 30	65997-17-3
Poly[oxy(methyl-1,2-ethanediyl)], α -hydro- ω -hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether bis-[4-(2,3-epoxipropoxy)phenyl]propane	7 – 13	72244-98-5
Zinc sulphide	7 – 13	1675-54-3
2,4,6-tris(dimethylaminomethyl)phenol	0.5 – 1.5	1314-98-3
crystalline silica, respirable powder (<10 microns)	0.5 – 1.5	90-72-2
	0.1 – 1	14808-60-7

SUB codes represent substances without registered CAS numbers.

Any concentration shown as a range to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: FIRST AID MEASURES

See toxicological information (Section 11)

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media:

Suitable extinguishing media:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media:	None known.
Specific hazards arising from the chemicals:	No specific fire or explosion hazard.

Hazardous thermal decomposition products: Decomposition products may include the following materials: carbon dioxide, nitrogen oxides, sulfur oxides, halogenated compounds, metal oxide/oxides.

Special protective actions for fire-fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small Spill: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large Spill: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling:

Conditions for safe storage, including any incompatibilities: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Protective measures: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Special precautions: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limits:

Ingredient name	Exposure Limits
Talc, not containing asbestiform fibers	ACGIH TLV (United States, 1/2025). TWA 8 hours: 2 mg/m ³ . Form: Respirable fraction OSHA PEL Z3 (United States). TWA: 2 mg/m ³
Glass, oxide, chemicals	OSHA PEL (United States). TWA: 15 mg/m ³ TWA: 5 mg/m ³ Form: Respirable TWA: 15 mg/m ³ Form: Total dust ACGIH TLV (United States). TWA: 1. Form: Continuous filament glass fibers TWA: 5 mg/m ³ , (Inhalable) Form: Continuous filament glass fibers TWA: 3 mg/m ³ Form: Respirable TWA: 10 mg/m ³ Form: Total dust
bis-[4-(2,3-epoxipropoxy)phenyl]propane	None.
zinc sulphide	None.
2,4,6-tris(dimethylaminomethyl)phenol	None.

Poly[oxy(methyl-1,2-ethanediyl)], α -hydro-
 ω -hydroxy-, ether with
2,2-bis(hydroxymethyl)-1,3-propanediol
(4:1), 2-hydroxy-3-mercaptopropyl ether

None.

Crystalline silica, respirable powder (<10
Microns)

ACGIH TLV (United States, 1/2025). [Silica, crystalline]
TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction
OSHA PEL Z3 (United States, 6/2016).
TWA: 10 mg/m³ / (%SiO₂+2) 8 hours. Form: Respirable
TWA: 250 mppcf / (%SiO₂+5) 8 hours. Form: Respirable

Key Abbreviations

A = Acceptable Maximum Peak
ACGIH = American Conference of Governmental Industrial Hygienists.
C = Ceiling Limit
F = Fume
IPEL = Internal Permissible Exposure Limit
OSHA = Occupational Safety and Health Administration.
R = Respirable
Z = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances
S Potential skin absorption
SR = Respiratory sensitization
SS = Skin sensitization
STEL = Short term Exposure limit values.
TD = Total dust
TLV = Threshold Limit Value
TWA = Time Weighted Average

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards.
Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls:

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be

allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection:

Chemical splash goggles.

Skin protection

Hand protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves – butyl rubber

Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product

Other skin protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection:

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid.	Solubility:	Insoluble in the following materials: cold water
Color:	Not available.		
Odor:	Not available.		
Odor threshold:	Not available.	Partition coefficient: n-octanol/water	Not applicable.
pH:	Not applicable.	Viscosity:	Kinematic (40°C (104°F)): Not applicable.
Melting point:	Not available.		
Boiling point:	Not available.	Volatility:	0% (v/v), 0% (w/w)
Flash point:	Closed cup: Not applicable.	% Solid. (w/w):	100
Evaporation rate:	Not available.	Particle Characteristics:	
Flammability (solid, gas):		Median particle size	Not available
Lower and upper explosive (flammable) limits:	Not available.		
Vapor pressure:	Not available.		
Vapor density:	Not available.		
Relative density:	1.95		
Density (lbs/gal)	16.27		

SECTION 10: STABILITY AND REACTIVITY

Reactivity:	No specific test related to reactivity available for this product or its ingredients.
Chemical stability:	Stable
Possibility of hazardous reactions:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid:	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products:	Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxypropoxi)	LD50 Dermal	Rabbit	23000 mg/kg	-

phenyl]propane	LD50 Oral	Rat	15000 mg/kg	
2,4,6-tris (dimethylaminomethyl)phenol	LD50 Dermal LD50 Oral	Rat Rat	1280 mg/kg 1200 mg/kg	-
Conclusion/Summary	There are no data available on the mixture itself.			

Skin Irritation/Corrosion

<u>Product/ingredient name</u>	<u>Result</u>	<u>Species</u>	<u>Score</u>	<u>Exposure</u>	<u>Observation</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Skin – Erythema/Eschar	Rabbit	0.8	4 hours	
	Skin – Edema	Rabbit	0.5	4 hours	
	Skin – Mild irritant	Rabbit	-	4 hours	
Conclusion/Summary	There are no data available on the mixture itself				

Serious eye damage/eye irritation

<u>Product/ingredient name</u>	<u>Result</u>	<u>Species</u>	<u>Score</u>	<u>Exposure</u>	<u>Observation</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Eyes – Redness of the conjunctivae	Rabbit	0.4	24 hours	
	Eye – Mild irritant	Rabbit	-	24 hours; fully reversible in 7 days or less	
Conclusion/Summary	There are no data available on the mixture itself				

Respiratory corrosion/irritation: There is no data available on the mixture itself.

Sensitization:

<u>Product/ingredient name</u>	<u>Route of Exposure</u>	<u>Species</u>	<u>Result</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Skin	Mouse	Sensitizing

Conclusion/Summary Skin/Respiratory:
There are no data available on the mixture itself.

Mutagenicity No specific data.

Carcinogenicity No specific data.

Classification

<u>Product/ingredient name</u>	<u>OSHA</u>	<u>IARC</u>	<u>NTP</u>
crystalline silica respirable powder (<10 microns)	+	1	Known to be a human carcinogen.
bis-[4-(2,3-epoxipropoxy)phenyl]propane	-	3	-
Glass, oxide, chemicals	-	3	

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

Reproductive toxicity: No specific data.

Teratogenicity: No specific data.

Specific target organ toxicity (single exposure):

<u>Product/ingredient name</u>	<u>Category</u>	<u>Route of exposure</u>	<u>Target Organs</u>
Talc, not containing asbestiform fibers	3	-	Respiratory tract irritation.

Specific target organ toxicity (repeated exposure):

<u>Product/ingredient name</u>	<u>Category</u>	<u>Route of exposure</u>	<u>Target Organs</u>
Crystalline silica, respirable powder (<10 microns)	1	Inhalation	-

Target organs: Contains material which may cause damage to the following organs: lungs, Cardiovascular system, upper respiratory tract, skin, eyes.

Information on the likely routes of exposure:**Potential acute health effects**

Eye contact:	Causes serious eye irritation.
Inhalation:	May cause respiratory irritation.
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.
Ingestion:	No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact:	Adverse symptoms may include the following: pain or irritation, watering redness.
Inhalation:	Adverse symptoms may include the following: respiratory tract irritation, coughing.
Skin Contact:	Adverse symptoms may include the following: irritation, redness.
Ingestion:	No specific data

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary: There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate effects: Not available.
Potential delayed effects: Not available.

Long term exposure

Potential immediate effects: Not available.
Potential delayed effects: Not available.

Potential chronic health effects: No specific data.

General:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity:	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity:	No known significant effects or critical hazards.
Reproductive toxicity:	No known significant effects or critical hazards.

Numerical measures of toxicity:

<u>Acute toxicity estimates</u>	<u>Oral (mg/kg)</u>	<u>Dermal (mg/kg)</u>	<u>Inhalation (gases)(ppm)</u>	<u>Inhalation (vapors) (mg/l)</u>	<u>Inhalation (dusts and mists) (mg/l)</u>
2001	75023.0	29834.9	N/A	N/A	N/A
bis-[4-(2,3-epoxipropoxy)phenyl]propane	15000	23000	N/A	N/A	N/A
2,4,6-tris(dimethylaminomethyl)phenol	1200	1280	N/A	N/A	N/A

SECTION 12: ECOLOGICAL INFORMATION**Toxicity:**

<u>Product/ingredient name</u>	<u>Result</u>	<u>Species</u>	<u>Exposure</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Acute LC50 1.8 mg/l Fresh Water Chronic – NOEC 0.3 mg/l	Daphnia-daphnia magna Daphnia	48 hours 21 days
2,4,6-tris (dimethylaminomethyl) phenol	Acute LC50 OECD >100 mg/l Acute LC50 OECD >100 mg/l	Daphnia Fish	48 hours 96 hours

Persistence and degradability:

<u>Product/ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Dose</u>	<u>Inoculum</u>
bis-[4-(2,3-epoxipropoxy) phenyl]propane	OECD closed bottle test	4% - 28 days Not readily	-	-

Bioaccumulative potential:

<u>Product/ingredient name</u>	<u>LogP_{ow}</u>	<u>BCF</u>	<u>Potential</u>
2,4,6-tris (dimethylaminomethyl) phenol	0.219	-	low

Mobility in soil - Soil/water partition coefficient (K_{oc}): Not available.

SECTION 13: DISPOSAL CONSIDERATIONS**Disposal Methods:**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

SECTION 14: TRANSPORT INFORMATION

	<u>DOT Classification</u>	<u>IMDG</u>	<u>IATA</u>
UN Number:	Not regulated	Not regulated	Not regulated
UN Proper Shipping Name:	-	-	-
Environmental Hazard:	No	No	No
Marine Pollutant substances	Not applicable	Not applicable	Not applicable
Transport Hazard class(es)	-	-	-

Special precautions for user: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: REGULATORY INFORMATION**U.S. Federal regulations:**

United States inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304 Composition/information on ingredients: No products were found.

SARA 304 RQ: Not applicable.

SARA 311/312:

Classification: SKIN IRRITATION – Category 2; EYE IRRITATION – Category 2A; SKIN SENSITIZATION – Category 1; CARCINOGENICITY – Category 1A; SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) – Category 3

Composition/information on ingredients:

<u>Name</u>	<u>%</u>	<u>Classification</u>
Talc, not containing asbestiform fibers	≥20 - ≤50	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Poly[oxy(methyl-1,2-ethanediyl)], α -hydro- ω -hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	≥10 - ≤20	SKIN SENSITIZATION – Category 1B
bis-[4-(2,3-epoxipropoxy)phenyl] propane	≥10 - ≤20	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1B
zinc sulphide	≥1.0 - ≤5.0	EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1B
2,4,6-tris(dimethylaminomethyl) phenol	≤1.0 - <3	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 SKIN CORROSION - Category 1C SERIOUS EYE DAMAGE - Category 1
crystalline silica, respirable powder (<10 microns)	<1.0	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

SARA 313 Form R Reporting requirements:

Product Name: zinc sulphide **CAS number:** 1314-98-3 **%:** 0.5 – 1.5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

California Prop. 65:

WARNING: Cancer – www.P65warnings.ca.gov

SECTION 16: OTHER INFORMATION

Hazardous Material Information System (U.S.A.)

Health: 3 * Flammability: 0 Physical hazards: 0

(*) – Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

National Fire Protection Association (U.S.A.)

Health: 3 Flammability: 0 Instability: 0

Key to abbreviations :

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

UN = United Nations

Important Note: *To be the best of our knowledge, the information contained herein is accurate. However there is no assumption of liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer/supplier, the manufacturer/supplier will not be responsible for loss, injury, or expense arising out of the products improper use. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.*

End of SDS