# SAFFTY DATA SHFFT



**SECTION 1: IDENTIFICATION** 

COMPANY NAME: AMERICAN INDUSTRIES, INC. PRODUCT NAME: HT MOLY (TUBES)

ADDRESS LINE 1: 4300 Kahn Drive, Box 1405 PRODUCT CODE: 1683

ADDRESS LINE 2: Lumberton, NC 28359-1405 USA PRODUCT USE: High Temperature Grease

 TELEPHONE NUMBERS:
 800-753-5153 (or) 910-738-7224
 SDS FILE ID:
 1683.02

 EMERGENCY PHONE:
 CHEMTREC 1-800-424-9300
 SDS DATE:
 2015-06-01

**REPLACES VERSION DATED:** 2013-05-09 and all prior versions

**SECTION 2: HAZARDS IDENTIFICATION** 

OSHA/HCS status This material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

Label elements OSHA HCS 2012

Health hazard Not expected to be a health hazard when used under normal conditions. Prolonged

or repeated skin contact without proper cleaning may clog the skin pores resulting disorders like acne/folliculitis. Used grease may contain harmful impurities/ harmful

extraneous substances.

Safety hazard Not classified as flammable but will burn.

Environmental hazard Not classified as environmental hazard under GHS criteria.

Precautionary statements

Prevention Wear protective gloves while handling. Wear eye and face protection. Wash hand

thoroughly after handling.

Response If on skin, wash with plenty of soap and water. Remove contaminated cloth and wash

thoroughly before use. If skin irritation occurs, get medical advice. If in eyes, wash with water for several minutes, in case of contact lenses, remove and wash with

plenty water. In case of irritation, get medical attention.

Storage Store the product in well-ventilated area. Keep the container straight lid upside. Do

not lay down upside down or do not keep container horizontally. This product has

natural tendency to squeeze oil if not kept properly.

Disposal Take expert advice of local regulatory agency for disposing this product.

Hazards not otherwise classified None as classified under 29 CFR 1900.1200

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

This material is defined as mixture and has no known hazards under GHS classification.

As per 29 CFR 1910.1200 paragraph (i), formulation is considered as trade secret and therefore specific chemical names and their percentages of components used have not been disclosed. The details about their specific chemical names and their percentages may be provided on request to health professionals, authorized representatives of regulatory authority, employees concerned in accordance with applicable provisions of this paragraph

## **SECTION 4: FIRST AID MEASURES**

General Not expected to be health hazard if used under normal conditions.

Inhalation Under normal conditions of intended use, this material is not expected to be

inhalation hazard. If some symptom exists, remove to fresh air. If not breathing,

give artificial respiration. Get medical attention

Skin contact Remove contaminated clothes. Flush exposed area with plenty of water followed by

washing by soap, if available. If persistent irritation occurs, obtain medical attention. If product is injected into or under the skin due to any reason, the victim, regardless of size or appearance of wound, victim should be brought immediately to medical attention for emergency surgical needs. Though the initial symptoms due to high pressure injection may be minimal / absent, early surgical treatment may significantly

reduce the extent of injury.

Eye contact Immediately flush with large quantities of cool water for at least 15 minutes. Get medical attention. Ingestion In general no treatment is necessary unless large quantities are swallowed; however, it is advisable to take medical attention. Do not induce vomiting unless directed by medical personnel. Do not give anything by mouth to an unconscious person. Self-protection of first-aiders When administering the first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings. **SECTION 5: FIRE-FIGHTING MEASURES** Suitable extinguishing media Water Spray (fog), dry chemical, foam, or carbon dioxide, sand to extinguish flames. Unsuitable extinguishing media Water stream may splash burning liquid and spread fire. Hazardous combustion product may include a complex mixture of airborne solid and Specific hazards arising from the chemical liquid particulates and gases (smoke), carbon monoxide, unidentified inorganic and organic compounds. Protective equipment and precautions for Proper protective equipment include chemical resistant gloves to be worn, chemical firefighters resistant suit is recommended when large contact with spill product is expected. Selfcontained breathing apparatus (SCBA) must be worn when approaching a fire in confined area. Select the fire fighters clothing approved by relevant standard **SECTION 6: ACCIDENTAL RELEASE MEASURES** Fully encapsulating, vapor protective clothing should be worn for spills and leaks with Personal precautions, protective equipment no fire. Do not touch and walk through spill area. Do not touch damaged container or and emergency procedures spilled material unless wearing appropriate protective clothing/equipment. Ventilate the closed area. **Emergency procedures** Isolate the spill / leak area in all directions for about 50 meters (150 ft) for liquids and about 25 meters (75 ft.) for solids and semi-solids. Eliminate all ignition sources (no smoking, flares, sparks / flames in close vicinity). Keep unauthorized persons away and ventilate closed space before entering. **Environmental precautions** Use appropriate measures for containment of spilled material to the environment. Prevent from entering/ spreading to drain, water, river, ditches by using sand, earth, floor dryers or other appropriate barriers. Methods and materials for containment and Shovel into suitable properly marked container for disposal or reclamation in accordance with local regulations. cleaning up Reference to other sections Refer to section 8 – exposure control / personal protection and section 13disposal considerations. **SECTION 7: HANDLING AND STORAGE General Precautions** Store in well-ventilated area, if risk of vapor inhalation. Use the information in this data sheet as input for risk management arising due to local conditions which help to manage safe handling of this product. Precautions for safe handling Avoid prolonged and repeated contact with skin. Avoid inhaling the vapors/mist. When handling the drums, kegs, pails etc., proper safety shoes, and other protective clothes, safety glasses etc. should be worn. Dispose appropriately any contaminated rags/material as per prevailing local allowable practices. Keep containers in closely tight and, cool and well ventilated areas. Keep containers tightly closed in well-ventilated covered areas. Avoid contact Conditions for safe storage, including any with rain or other water sources. Keep the storage place cool preferably <120 °F / incompatibilities <50 °C. Higher temperature may create pressure buildup inside container and chances of container bursting or leakage may occur under extreme conditions. Keep away from other oxidizing and incompatible materials. This material should not be used for any other purpose than the intended use as Specific End Use (s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

per section 1 without the expert advice

Crystalline silica (Quartz) ACGIH TWA 0.025 mg/m<sup>3</sup>

TLV

Molybdenum Di Sulphide ACGIH - 10.0 mg/m<sup>3</sup>

Additional information Due to semi-solid nature of the product, generation of mist and dusts is unlikely to

occur.

Biological exposure index (BEI) No biological limit allocated.

PNEC related information Data not available.

Monitoring methods Monitoring of the concentration of substances in the breathing zone of

workers or in general workplace may be required to confirm the compliance

with local governing authority.

Engineering measures/controls Adequate ventilation systems may be needed to control concentrations of

 $\ airborne\ contaminants\ above\ permissible\ threshold\ applicable\ limits.$ 

Respiratory In case of insufficient ventilation, use suitable respiratory equipment.

Eye/face protection Wear safety goggles.

Skin/body protection Wear safety shoes and protective gloves.

Environmental exposure controls Minimize release to the environment. Follow best practices for site management and

disposal of waste as per local regulations

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance** 

Physical state Semi-solid Color Black

Slight hydrocarbon Odor Odor Threshold Not available **Boiling point** Not available На Not applicable 0.87, 7.506 (lbs/gal) Specific gravity (15°C) (59°F) Flash point, COC, 204°C (400°F) Lower and upper flammability limits Not available Auto-ignition temperature Not available Flammability Not available

VOC, % wt. ASTM D-972

Vapor pressure @ ambient temp. < 0.13 kPa (< 1 mm Hg)

Vapor density (air =1) <1

Explosive properties Not classified
Oxidizing properties No data available

Electrical conductivity Though no data available, this material is not expected to be a static accumulator.

**SECTION 10: STABILITY AND REACTIVITY** 

Reactivity No reactivity is expected under normal conditions of intended use. However, under

high temperature or adverse operating conditions thermal / chemical decomposition

of the product may be possible.

Chemical stability

No hazardous reaction is expected under normal conditions of temperature and

pressure.

Possibility of hazardous reactions Hazardous polymerization is not expected. Reacts with strong oxidizing agents.

Conditions to avoid Extreme temperature and direct sunlight / heat /flame.

Incompatible materials Strong oxidizing agent.

Hazardous decomposition products

Hazardous decomposition is not expected to form under normal conditions of

storage.

**SECTION 11: TOXICOLOGICAL INFORMATION** 

Basis of assessment Information given hereby is based on the components and the toxicology of similar

products and the data indicated here are representative of the base oil used to make

this product.

Acute oral toxicity Expected to be low toxicity; LD 50 (rat) > 5000 mg/kg

Acute dermal toxicity Expected to be low toxicity; LD 50 > (rat) 3000 mg/kg

Acute inhalation toxicity Not determined.

Skin Irritation/Corrosion Expected to be slightly irritating. Prolonged/repeated contact with skin without

adequate cleaning may clog the pores of the skin, may result disorder such as oil

acne/folliculitis.

Respiratory/skin sensitization Not determined.

Aspiration Not expected to be aspiration hazard.

Germ cell mutagenicity Not expected a mutagenic hazard.

Carcinogenicity Not considered to be carcinogenic as it contain severely refined which are reported to

be non-carcinogenic in lab animal studies. The class of oils used in making this

product are not classified as carcinogenic by IARC.

Material-Highly refined base oil blend

(IP 346 < 3%)

ACGIH group A4; not classified as human carcinogen IARC 3; not classified as to carcinogen to humans GHS/CLP, no carcinogenicity classification

This material is not known to contain any chemical listed as a carcinogen or suspected carcinogen by OSHA Hazard Communication Standard 29CFR 1910.1200, IARC, or the National Toxicology Program (NTP) at a concentration greater than 0.1%

# **SECTION 12: ECOLOGICAL INFORMATION**

Basis of assessment Eco-toxicological data has not been determined specifically on this product. The

information given herewith is based on the information given on eco-toxicity of components and/or on similar products. the information given here are representative of the product as whole and not as individual components

Toxicity Sparingly soluble mixture in aqueous media. Not toxic to fish but may coat gill

structure and cause suffocation if spilled. This product may cause gastrointestinal

distress in birds and mammals through ingestion.

Persistence and degradability Expected to be not readily biodegradable. The major oil component expected to

biodegrade over period of 100-120 days in aerobic environment at temperature above 70°F (21°C), however finished product contain component that may persist in

the environment.

Bioaccumulative potential Mau contain component that bioaccumulate.

Mobility in soil Product is semi-solid in nature in most conditions and may absorb to soil and may

not be mobile. It floats on water.

Other adverse effects Product contain the components that have been classified non-volatile in nature and

therefore not expected to release to environment in significant quantities.

**SECTION 13: DISPOSAL CONSIDERATIONS** 

Product disposal Try to minimize the product waste by using best applicable practices. It is the

responsibility of the waste generator to evaluate the waste classification and appropriate disposal methodology in accordance with the applicable regulation. Do not dispose in to environment, in drain or in river / ponds / water reservoirs.

To be disposed in accordance with local prevailing and allowable regulations

Container disposal To be disposed in accordance with local prevailing and allowable regulations

**SECTION 14: TRANSPORT INFORMATION** 

US DOT Not required.
Canadian TDG Not required.
European Not required.

ADR, IMDG, IATA-DGR Not classified as hazardous product for land, sea and air transport.

**SECTION 15: REGULATORY INFORMATION** 

OSHA Hazard Communication Standard This material is not considered hazardous in accordance with OSHA HAzCom 2012,

29 CFR 1910.1200.

US inventory list All components are listed or exempted. (TSCA 8b)

SARA 302/304

SARA 311/312

No products were found.

Classification

Component Fire hazard

No

Crystalline Silica (Quartz) No Molybdenum disulphide No

SARA 313 Toxic Release Inventory

**New Jersey** 

Base oil

California 65

WHMIS

Canadian NPRI

CEPA toxic substance

Europe (EINECS/ELINCS/NLP)

Australia Inventory (AICS)

China Inventory (IECSC)

Japan Inventory

Korea Inventory

New Zealand inventory of Chemicals (NZIoC)

Philippines Inventory (PICCS)

Immediate (acute) health hazard, delayed (chronic) health hazard

Sudden release of Reactive Acute health Delayed health hazard hazard pressure No No No Yes No No Yes Yes No No Yes Yes

This material contains no chemicals subject to the supplier notification requirements

of the SARA 313 Toxic Release Program.

Petroleum is listed.

Crystalline silica ( quartz ) is known cause cancer and / or developmental effect .

This product is not a controlled product.

None of the components are listed.

None of the components are listed.

All components are listed or exempted from EU listing requirements.

All components are listed or exempted.

All components are listed or exempted.

Not determined.

All components are listed or exempted.

Not determined.

All components are listed or exempted.

All components are listed or exempted.

### **SECTION 16: OTHER INFORMATION**

Malaysia Inventory (EHS Register)

Hazardous Materials Identification System (HMIS)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks.

**Important Note:** To be the best of our knowledge, the information contained herein is accurate. However there is no assumption of liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer/supplier, the manufacturer/supplier will not be responsible for loss, injury, or expense arising out of the products improper use. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

\*\*\*End of SDS\*\*\*