SAFETY DATA SHEET



SECTION 1: IDENTIFICATION

COMPANY NAME: AMERICAN INDUSTRIES, INC. PRODUCT NAME: SIL-O-RING ADDRESS LINE 1: 4300 Kahn Drive, Box 1405 PRODUCT CODE: 1667

ADDRESS LINE 2: Lumberton, NC 28359-1405 USA PRODUCT USE: O-Ring Lubricant

 TELEPHONE NUMBERS:
 800-753-5153 (or) 910-738-7224
 SDS FILE ID:
 1667.02

 EMERGENCY PHONE:
 CHEMTREC 1-800-424-9300
 SDS DATE:
 2015-06-01

REPLACES VERSION DATED: 2011-01-01 and all prior versions

SECTION 2: HAZARDS IDENTIFICATION

Classification Not hazardous

Labeling None
Signal word None

Hazard statement: Not hazardous.

Avoid contact with eyes.

Non flammable or combustible, but may burn if involved in a fire.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u> <u>CAS number</u> <u>%</u> <u>Impurities</u>

Dimethyl siloxanes and silicones (Methyl 63148-62-9 100 No information provided by

silicone) manufacturer

SECTION 4: FIRST AID MEASURES

Inhalation If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical

attention.

Skin contact Wash affected area with soap and water. If signs/symptoms persist, get medical attention. No

need for first aid is anticipated.

Eye contact Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. Obtain

medical attention.

Ingestion If swallowed, do not induce vomiting. If irritation or discomfort occurs, obtain medical assistance.

SECTION 5: FIRE-FIGHTING MEASURES

Autoignition temperature >300°C (572°F)
Flashpoint >300°C (572°F)
Flammable Limits (LEL) Not determined.
Flammable Limits (UEL) Not determined.

Suitable extinguishing media On large fires used dry chemical, foam, or water spray. On small fires use carbon dioxide, dry

chemical, or water spray. Water can be used to cool fire exposed containers.

Unsuitable extinguishing media None.

Specific hazards in case of fire Decomposes on heating and can release formaldehyde. Avoid reaction with oxidizers.

Special firefighting protective equipment and precautions

No acute hazard. Move container from fire area, if possible. Avoid breathing vapors or dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a

separate escape air supply. Use any self contained breathing apparatus with a full face piece.

Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing.

Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If safe to do so, remove containers from path of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Environmental precautions For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of

water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Methods for material containment and cleaning up Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin, inhalation of mist, or ingestion. See section 8 for personal protection equipment. Practice good personal hygiene to prevent accidental ingestion after handling. Properly dispose of clothing that cannot be decontaminated.

Conditions for safe storage, including any incompatibilities Store away from oxidizing materials. Store product in a closed container located in a dry area. Do not store in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters Under most handling conditions, this product will not generate mist or dust.

In most conditions, no special local ventilation is needed. General ventilation recommended. If **Engineering controls**

the product is heated above 150°C (302°F) or atomized ventilation should be used.

Safety glasses recommended. Eyes

Skin Impermeable gloves should be worn. Product is compatible with most elastomers.

Inhalation No respiratory protection required under most conditions. If concentrations exceed exposure

limits, approved respiratory equipment must be used.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical Liquid Color Colorless

Characteristic, mild Odor Odor threshold Not available Not applicable -23°C (-9.4°F) Melting point

Freezing Point 33°C (-27.4°F) (pour point)

Initial Boiling point >200°C (392°C) Flash point >321°C (609.8°F) COC

Evaporation Rate Not available Not applicable Flammability (solid, gas) **Explosion limits** Not available

Negligible at 20°C (68°F) Vapor Pressure

Vapor density Not avialable

Solubility Insoluble in water at 20°C (68°F)

Partition Coefficient Not available Auto-ignition temperature Not available

Begins to decompose at 150°C (302°F) **Decomposition Temperature**

SECTION 10: STABILITY AND REACTIVITY

Chemical stability Stable under ambient temperatures and pressures.

Possible hazardous reactions May react with air under very high pressure. Otherwise will not react or polymerize.

Conditions to avoid No specific conditions to avoid have been identified.

Oxidizes Materials to avoid

Hazardous decomposition

products carbon compounds.

Decomposes on heating and produces formaldehyde, silicone dioxide, and incompletely burned

SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity Not toxic. LD₅₀ (rat) > 10,000 mg/kg.

Skin corrosion/irritation Not irritating / not corrosive to the skin. LD50 (rabbit) > 2,000 mg/kg.

Serious eye damage/irritation Possible irritant/not corrosive to the eyes.

Respiratory or skin sensitization Not sensitizing to the skin. Germ cell mutagenicity Not a germ cell mutagen

SDS File ID: 1667.02 Product Name: SIL-O-RING SDS Issue/Revision Date: 06/01/15 AMERICAN INDUSTRIES, INC. Page 2 of 4 Carcinogenicity Not a carcinogen.

Reproductive toxicity There are currently no reliable scientific data available indicating adverse effects on reproduction

or fertility.

Aspiration hazard Not applicable (not an aerosol/mist).

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Invertebrates: Daphnia magna 48h-LC50 > 10,000 mg/L

Persistence and degradability In soil, siloxanes are degraded.

Bioaccumulative potential This product is not expected to bioaccumulate.

Mobility in soil Siloxanes are removed from water by sedimentation or binding to sewage sludge.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods Waste (substance and container material) shall be recycled/recovered or disposed of as

applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site.

Recycle containers if possible, or dispose of in an authorized landfill.

According to the European

waste catalogue

Waste Codes are not product specific but application specific. Waste Codes should be assigned by

the user based on the application in which the product is used.

For USA disposal Waste must be disposed of in accordance with federal, state, and local environmental control

regulations.

SECTION 14: TRANSPORT INFORMATION

Class US,IMO, ADR, RID, AND, Non-hazardous

or IMDG, IATA

type

SECTION 15: REGULATORY INFORMATION

TSCA Status: All ingredients are listed or exempt.

TSCA 12 (b) Export Notification: Not listed. CERCLA Section 103 (40 CFR 302.4): N

SARA Section 302 (40 CFR 355.30): N

SARA Section 304 (40 CFR 355.40): N

SARA Section 313 (40 CFR 372.65): N
OSHA Process Safety (29 CFR 1910.119): N

SARA Hazard Categories, SARA Sections 311/312 (40 CFR 370.21)

Acute Hazard: N Chronic Hazard: N Fire Hazard: N Reactivity Hazard N

Sudden Release Hazard: N

State Regulations: Not on California Proposition 65 list. Does not contain any contaminants or by-products known to the State of California to cause cancer or reproductive toxicity.

Note – There are no known safety, health or environmental restrictions or prohibitions in any country where this product is produced, imported or marketed.

Chemical Inventories:

DSL (Canada) All ingredients listed or exempt

EINECS (European Union) All ingredients listed or exempt.

ENCS/ISHL (Japan) All ingredients listed or exempt.

IECSC (Peoples Republic of China) All ingredients listed or exempt

TSCA (United States of America) All ingredients listed or exempt

SDS File ID: 1667.02 Product Name: SIL-O-RING SDS Issue/Revision Date: 06/01/15 AMERICAN INDUSTRIES, INC. Page 3 of 4

SECTION 16: OTHER INFORMATION

Hazardous Materials Identification System (HMIS)



Important Note: To be the best of our knowledge, the information contained herein is accurate. However there is no assumption of liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer/supplier, the manufacturer/supplier will not be responsible for loss, injury, or expense arising out of the products improper use. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

End of SDS

SDS File ID: 1667.02 Product Name: SIL-O-RING SDS Issue/Revision Date: 06/01/15 AMERICAN INDUSTRIES, INC. Page 4 of 4